

**CP-UVR-1616K1-H****16 Ch. 1080P H.265 Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 6MP IP Camera
- Max 96Mbps Incoming Bandwidth
- H.265+ / H.265 dual-stream video compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 10TB, 2 USB Ports
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UVR-1616K1-H

## 16 Ch. 1080P H.265 Cosmic HD DVR



### Feature

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
User Interface  
Video Input  
Video Output  
Video Standard  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Bit Rate  
Audio Input  
Audio Output  
Motion Detection  
Video Loss  
Audio Compression  
Camera Blank  
Alarm Input  
Alarm Output  
Smart Phone  
Audio Sample Rate  
Hard Disk  
Audio Bit Rate  
Trigger Events  
Recording Mode  
Search Mode  
Playback

### Specification

Embedded processor  
16+8 Ch. : each channel up to 6MP  
Embedded LINUX  
Reuse audio in/out, RCA  
GUI  
16 channel, BNC  
1 HDMI, 1 VGA  
Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)  
H.265+/H.265/H.264+/H.264  
1920×1080, 1280×1024, 1280×720  
Main stream: 4M-N/1080P(1~15fps); 1080N/720P/960H/ D1/CIF (1~25/30fps), Sub stream: D1/CIF(1~15fps)  
1/4/8/9/16  
32Kbps ~ 6144Kbps Per Channel  
16 channel  
3 channel  
MD Zones: 396 (22 × 18)  
Supports  
AAC (only for the 1st channel), G.711A, G.711U, PCM  
Supports  
16 channel  
3 channel  
iPhone, iPad, Android, Phone  
8KHz, 16 bit Per Channel  
1 SATA port, up to 10TB  
64Kbps Per Channel  
Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips  
Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop  
Time /Date, Alarm, MD and Exact Search (accurate to second)  
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom



# CP- UVR-1616K1-H

16 Ch. 1080P H.265 Cosmic HD DVR



## Feature

Backup Mode

Interface Ports

Max User Account

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

## Specification

USB Device/Network

1 HDMI, 1 VGA, 2 USB Ports(1 USB 2.0 , 1 USB 3.0), 1 RS485

128 users

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

RJ-45 port (1000M)

HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server,P2P, IP Search, ONVIF 16.12, CGI Conformant

DC12V/2A

<15W(without HDD)

-10 ~+55°C / 10~90%RH

325mm x 255mm x 55mm

1.3KG (without HDD)