

**CP-UVR-3201E2-H****32 Ch. 1080P Lite H.265 Cosmic HD DVR****Main Features**

- Auto Adaptive HDCVI/AHD/TVI/CVBS/IP signals
- Support upto 6MP IP Camera
- Max 64Mbps Incoming Bandwidth
- H.265 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 10TB Each, 2 USB Ports
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UVR-3201E2-H

## 32 Ch. 1080P Lite H.265 Cosmic HD DVR



### Feature

Processor  
 IP Camera Input  
 Operating System  
 Two-way Talk  
 User Interface  
 Video Input  
 Video Output  
 Video Standard  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Audio Input  
 Audio Output  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Audio Compression  
 Hard Disk  
 Audio Sample Rate  
 Smart Phone  
 Audio Bit Rate  
 Trigger Events  
 Recording Mode  
 Search Mode  
 Playback  
 Backup Mode  
 Interface Ports

### Specification

Embedded processor  
 16Ch. : each channel up to 6MP  
 Embedded LINUX  
 Reuse audio in/out, RCA  
 GUI  
 32 channel, BNC  
 1 HDMI, 1 VGA, 1 TV  
 Analog: NTSC(525Line, 60f/s), PAL(625Line, 50f/s)  
 H.265/H.264  
 1920×1080, 1280×1024, 1280×720  
 Main Stream: the 1st channel 1080N/720P(1~25/30fps), others 1080N/720P(1~15fps); 960H/D1/CIF (1~25/30fps), Sub stream: CIF (1~7fps)  
 1/4/8/9/16/25/36  
 1 channel, RCA  
 1 channel, RCA  
 MD Zones: 396 (22 × 18)  
 Supports  
 Supports  
 AAC (only for the 1st channel), G.711A, G.711U, PCM  
 2 SATA port, up to 10TB Each  
 8KHz, 16 bit Per Channel  
 iPhone, iPad, Android Phone  
 64Kbps Per Channel  
 Recording, PTZ, Tour, Alarm Out, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips  
 Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop  
 Time /Date, Alarm, MD and Exact Search (accurate to second)  
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom  
 USB Device/ Network  
 1 HDMI, 1 VGA, 2 USB Ports(1 USB 2.0 , 1 USB 3.0), 1 RS485



**CP-UVR-3201E2-H****32 Ch. 1080P Lite H.265 Cosmic HD DVR****Feature**

Max User Account

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

**Specification**

128 users

1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

1 RJ-45 Port (1000M)

HTTP, HTTPS, TCP/IP, IPv4/IPv6, Wi-Fi, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search, ONVIF 16.12, CGI Conformant

DC12V/5A

&lt;20W(without HDD)

-10 ~+55°C / 10~90%RH

375mm×287mm×53mm

1.9kg (without HDD)