

CP- VNC-D51ZR3C-MD**5 MP Full HD WDR Array Dome Camera - 30Mtr.****Main Features**

- 1/2.7" 5MP PS CMOS Image Sensor
- 5MP(2592 x 1944): Max. 25 fps
- Ultra 265,H.265, H.264, MJPEG Triple-stream Encoding
- WDR(120dB), Day/Night (ICR), 2D/3D-DNR,Corridor mode, ROI, Digital defog, AWB, AGC, BLC, HLC
- 2.7~13.5 mm Motorized Lens
- Array Range of 30 Mtrs, Smart IR, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS

**InstaStream**

CP- VNC-D51ZR3C-MD

5 MP Full HD WDR Array Dome Camera - 30Mtr.

Feature

Image Sensor
 Minimum Illumination
 Shutter Speed
 White Balance
 Lens
 Gain Control (AGC)
 Video Compression
 Angle of View
 DORI Distance
 Back Light Compensation
 S/N Ratio
 Video Streaming
 Resolution
 Frame Rate
 Motion detection
 Privacy Mask
 ICR
 ROI
 Audio Compression
 Audio
 Protocol
 Dewarping
 Ethernet
 Network Storage
 OSD
 Smart Phone
 IR
 Micro SD

Specification

1/2.7" 5MP Progressive scan CMOS
 Colour: 0.002Lux (F1.2, AGC ON) 0Lux with IR
 Auto/Manual, shutter time: 1~1/100000 s
 Auto/Manual
 2.7~13.5 mm Motorized Lens
 Auto/Manual
 Ultra 265,H.265, H.264, MJPEG
 93.38° ~ 28.56° (H), 88° ~ 16.4° (V), 121.4° ~ 33.7°(O)
 2.7mm– 60.8 Detect (m) , 24.3 Observe (m), 12.2 Recognize (m), 6.1 Identify (m)
 13.5mm– 303.8 Detect (m) , 121.5 Observe (m), 60.8 Recognize (m), 30.4 Identify (m)
 BLC / HLC / WDR(120dB)
 >52dB
 Triple
 2592 x 1944
 Main Stream: 5MP (2592x1944), Max 20fps; 5MP (2592x1944), Max 25fps (WDR OFF); 4MP (2560x1440), Max 30fps; 3MP (2048x1536), Max 30fps; 2MP (1920x1080), Max 30fps;
 Sub Stream: 2MP (1920x1080), Max 30fps; Third Stream: D1 (720x576), Max 30fps
 Up to 4 areas
 Up to 8 areas
 IR-cut filter with auto switch (ICR)
 Up to 8 areas
 G.711
 Built-in Mic
 IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, ONVIF (Profile S, Profile G, Profile T), API
 Support
 10M/100M Base-TX Ethernet
 ANR, NAS(NFS)
 Up to 8 OSDs
 Android, ios
 Array Range of 30 Mtr., Smart IR
 Micro SD, up to 256GB

 **CP- VNC-D51ZR3C-MD****5 MP Full HD WDR Array Dome Camera - 30Mtr.****Feature**

Operating Temperature
Humidity
Casing
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

-40°C ~ 60°C (-40°F ~ 140°F)
≤95% RH (non-condensing)
Metal
12 V DC±25%, PoE (IEEE802.3 af)
Max. 8.16W
IP67
Φ129 x 110 mm (Ø5.08" x 4.3")
0.82kg