

CP- VNR-3832**32 Ch. 4K Network Video Recorder****Main Features**

- 32 Channel IP Camera Input
- Ultra H.265/H.265/H.264 Video Formats
- Support 4K Resolution Upto 12MP Recording
- 320Mbps Incoming/ 320Mbps Outgoing Bandwidth
- Support 8 SATA HDDs up to 10TB Each, 3 USB Ports
- Support N+1 Hot spare
- Support RAID 0, 1, 5, 6, 10
- Dewarping support for fisheye cameras
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3832

32 Ch. 4K Network Video Recorder

Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 HDMI/VGA Output
 Compression
 Recording Resolution
 Video Recording
 Video Display Split
 CVBS Output
 Live view/Playback
 Capability
 Corridor Mode Screen
 Audio Input
 Audio Output
 Alarm Input
 Alarm Output
 Hard Disk
 RAID
 Playback
 Interface Ports
 Ethernet
 Protocols
 Power Supply
 Power Consumption
 Working Temp
 Working Humidity

Specification

Dual-core embedded processor
 32 channel
 Embedded LINUX
 1 channel, RCA
 GUI
 HDMI1/VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
 HDMI2: 4K (3840x2160)/60Hz, 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
 Ultra H.265/ H.265 / H.264
 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 320Mbps
 1/4/8/9/16/32
 1 Ch, BNC
 12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
 3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080P@30, 32 x 960P@25
 3/4/5/7/9/10/12/16/32
 1 channel, RCA
 1 channel, RCA
 16 channel
 4 channel
 8 SATA ports, up to 10TB Each
 RAID 0,1, 5, 6,10
 16 Channel
 3 USB Port(2 x USB2.0,Rear panel: 1 x USB3.0), 1 RS485, 1 RS232, 1 eSATA Port
 2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
 P2P, UPnP, NTP, DHCP, PPPoE, ONVIF conformance: Profile S, Profile G, Profile T
 100 ~ 240V AC
 ≤ 20 W (without HDD)
 -10°C ~ + 55°C (+14°F ~ +131°F)
 ≤ 90% RH (non-condensing)

 **CP- VNR-3832****32 Ch. 4K Network Video Recorder****Feature**

Dimensions

Weight

Specification

442mm x425mmx 86mm (17.4" x 16.7" x 3.4")

≤ 5.13 Kg