

**CP- VNR-3104-4P****4 Ch. 4K 4PoE Network Video Recorder****INDIGO****Main Features**

- 4 Channel IP Camera Input
- H.265/H.264 dual Video Formats
- Support 4K Resolution Upto 8MP Recording
- 40Mbps Incoming/ 64Mbps Outgoing Bandwidth
- Support 1 SATA HDDs up to 8TB, 3 USB Ports, 4 PoE Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



# CP- VNR-3104-4P

## 4 Ch. 4K 4PoE Network Video Recorder



### Feature

Processor  
IP Camera Input  
Operating System  
Two-way Talk  
User Interface  
Video Output  
Compression  
Video Resolution  
Video Recording  
Video Display Split  
Audio Input  
Audio Output  
Alarm Input  
Alarm Output  
Hard Disk  
Playback  
Interface Ports  
Max User Account  
Ethernet  
Protocols  
Power Supply  
Power Consumption  
Working Temp  
Working Humidity  
Dimensions  
Weight

### Specification

Dual-core embedded processor  
4 channel  
Embedded LINUX  
1 channel, RCA  
GUI  
HDMI, VGA , 4K(3840 x 2160)@30Hz, 1920 x 1080P@60Hz, 1920 x 1080P@50Hz, 1600 x 1200@60Hz, 1280 x 1024@60Hz, 1280 x 720@60Hz, 1024 x 768@60Hz  
H.265 / H.264  
Upto 8MP, 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF  
40Mbps  
1/4  
1 channel, RCA  
1 channel, RCA  
4 channel  
1 channel  
1 SATA ports, up to 8TB  
4 Channel  
3 USB Port, 1 RJ45  
128  
1 RJ-45 10M/100M Self-adaptive Ethernet Interface, 4 independent 100 Mbps PoE Network  
HTTP, TCP/IP, IPV4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Server, P2P, ONVIF  
48V DC , PoE: IEEE 802.3at, IEEE 802.3af  
≤ 5 W , PoE: Max 30W for single port , Max 54W in total ( 13.5W for each )  
-10°C ~ + 55°C ( +14°F ~ +131°F )  
10% ~ 90%  
44mm × 260mm × 240mm ( 1.7" × 10.2" × 9.4" )  
≤ 1.12 Kg

