

CP- UNC-TE61ZL10E-VMD**6MP Full HD WDR IR Network Bullet Camera - 100Mtr.****Main Features**

- 1/2.9" 6MP PS CMOS Image Sensor
- 20fps@6MP(3072x2048),25/30fps@4MP(2688x1520)
- H.265 / H.264 triple-stream encoding
- WDR, Day/Night (ICR), 3D-DNR, AWB, AGC, BLC, HLC
- 7mm ~35mm Motorized Lens
- 2/1 Alarm in/out, 1/1 audio in/out
- IR Range of 100 Mtrs, Micro SD Card, IP67, IK10, ePoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-TE61ZL10E-VMD

6MP Full HD WDR IR Network Bullet Camera - 100Mtr.



Feature

Image Sensor
Effective Pixels
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control (AGC)
Angle of View
Video Compression
S/N Ratio
Back Light Compensation

Video Streaming

Resolution

Digital Zoom

Motion detection

Privacy Mask

ICR

ROI

Audio Input

Audio Output

Audio Compression

Alarm IN

Alarm Out

Bit Rate

Protocol

Smart Detection

Ethernet

User Account

Specification

1/2.9" 6MP Progressive scan CMOS
3072(H)x2048(V)
0.03Lux/F1.4 (Color,1/3s,30IRE) 0.3Lux/F1.4 (Color,1/30s,30IRE) 0Lux/F1.4(IR on)
Auto/Manual, 1/3~1/100000s
Auto/Natural/Street Lamp/Outdoor/Manual
7mm~35mm Motorized Lens
Auto/Manual
H:32°~10°, V:22°~8°
H.265+/H.265/H.264+/H.264
More than 50dB
BLC/ HLC/ WDR
Main Stream: 6MP(1~20fps)/4M(1~25/30fps), Sub Stream: D1(1~25/30fps), Third Stream: 720P(1~25/30fps)
6MP(3072x2048)/5MP(3072x1728)/ 5MP(2592x1944)/ 4MP(2688x1520)/ 3MP(2048x1536)/ 3MP(2304x1296)/ 1080P(1920x1080)/1.3M(1280x960)/ 720P(1280x720)/ D1 (704x576/704x480)/ VGA(640x480)/ CIF(352x288/352x240)
16x
Off / On (4 Zone, Rectangle)
Off / On (4 Area, Rectangle)
Auto (ICR)/Color/B/W
Off / On (4 Zone)
1 Channel
1 Channel
G.711a/ G.711Mu/ AAC/ G.726
2 channel In: 5mA 5VDC
1 channel Out: 300mA 12VDC
H.264: 24~10240Kbps , H.265: 14~9984Kbps
HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP; ONVIF; PSIA; CGI
Tripwire, Intrusion, Object Abandoned/Missing, Face Detection
RJ-45 (10/100Base-T)
20 Users



CP- UNC-TE61ZL10E-VMD**6MP Full HD WDR IR Network Bullet Camera - 100Mtr.****Feature**

IR
Smart Phone
Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

IR Range of 100 Mtr.
iPhone, iPad, Android Phone
Micro SD, Max 128GB
-30°C~+60°C, Less than 95% RH
DC12V, ePoE
<12.95W
IP67 & IK10
273.2mm x 95.0mm x 95.0mm
1.11Kg